

## FastFit™ Feature

FastFit™ motor gearbox attachment enable the windlass to be fitted by one man alone.

While the gearbox alignment to the deck unit is critical to a standard installation, the FastFit™ clamping system perfectly align the deck unit and motorgearbox for a perfect fit first time.

**A** FastFit™ enable the motor / gearbox to be rotated and fixed in increments of 45°

**B** To install your windlass, simply fix the deck unit to the deck and then slide the gearbox up the shaft, swing the FastFit™ clamp shut and tighten up the bronze nut.




## V1/V2/V3 Vertical Windlasses


Specify your V1/V2/V3

### 1 Deck Unit

PART NO. (Non FastFit)	PART NO. (FastFit)	DESCRIPTION
69000481	68000951	V1 Gypsy only
69000484	68000828	V2/3 Gypsy only
69000485	68000829	V2/3 Gypsy Drum




Gypsy and drum



Gypsy only

### 2 Motor Gearbox

PART NO. (Non FastFit)	PART NO. (FastFit)	DESCRIPTION
68001055	66810065	V1-12V
68000527	68000813	V2 - 12V
68000538	68000814	V2 - 24V
66810007	68000815	V3 - 12V
66810008	68000816	V3 - 24V



#### IP68 motor gearbox available (non FastFit™)

- Water resistant unit won't be damaged even if submerged under water
- Robust composite case
- Compression cable clamps included
- No maintenance required
- Provide best motor protection against the elements

PART NO.	DESCRIPTION
68001052	V2 12V IP68 Motor Gearbox Assy - No Cables
68001053	V2 24V IP68 Motor Gearbox Assy - No Cables
66810037	V3 12V IP68 Motor Gearbox Assy - No Cables
68001054	V3 24V IP68 Motor Gearbox Assy - No Cables

### 3 Gypsy

PART NO.	GYPSY NUMBER	CHAIN DESCRIPTION	ROPE SIZE		ROPE DESCRIPTION
			mm	in	
68000840	006	6mm ISO 4565, 1/4" G40*, 1/4" BBB	12-14	1/2	3-strand and 8-plait
68000360	000	7mm ISO 4565, 1/4" G40*, 1/4" BBB	12-14	1/2	3-strand and 8-plait
68000361	001	8mm DIN 766, 8mm ISO 4565	12-16	1/2 - 5/8	3-strand and 8-plait (5/8 only)
68000362	002	10mm DIN 766, Campbell 3/8" S4, 5/16" G40	12-16	1/2 - 5/8	3-strand and 8-plait (5/8 only)
68000363	003	10mm ISO, Campbell 3/8" S3, Lewmar 9.5mm G40	16	5/8	3-strand and 8-plait

\*G40 = Grade 40 Short Link Chain