

## Snatch block with snap shackle - Max rope size 12 mm

Part #34500



### Description

Free rotation thanks to snap shackle  
Very strong closing system  
Easy opening by simply pulling on the plunger pin.  
Shock and scratch-resistant thanks to the elastomer moulded cheeks

### Applications

Changing sheets  
Spinnaker sheet deflector blocks

## Technical information

Materials	HR 17.4 PH forged stainless steel arm Elastomer moulded cheeks Composite sheave
-----------	---------------------------------------------------------------------------------------

Rope size	Pour cordage de 12 m
-----------	----------------------

Length (mm)	145
-------------	-----

Width (mm)	59
------------	----

Thickness (mm)	43
----------------	----

 Working load (kg)	720
-------------------------------------------------------------------------------------------------------	-----

Breaking load (kg)	1300
--------------------	------

Weight (g)	254
------------	-----

### Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.  
The safety factor is 5 times the breaking load.  
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.