

ACCESSORI TENDALINI | BIMINI TOP ACCESSORIES

Cappuccio

End cap

Articolo-Item	€/pc.	Ø mm.
O 24 32 830 NEW		20
O 24 32 401		22
O 24 32 015		25
O 24 32 832 NEW		32

 **AISI 316**



Snodo a forcella

Fork joint

Articolo-Item	€/pc.	Ø mm.
O 24 32 020 NEW		20
O 24 32 405		22
O 24 32 030		25
O 24 32 032 NEW		32

 **AISI 316**



Supporto forcella 90°

90° Fork joint

Articolo-Item	€/pc.
O 24 32 090	

 **AISI 316**



Supporto forcella 90° c/perno a molla

90° Fork joint with spring pin

Articolo-Item	€/pc.
O 24 32 177	

 **AISI 316**



Supporto forcella inclinata con perno a molla

Slanting fork joint with spring pin

Articolo-Item	€/pc.
O 24 32 178	

 **AISI 316**



Supporto forcella 90° attacco a tubo

90° Fork joint with spring pin for pipe

Articolo-Item	€/pc.
O 24 32 179	

 **AISI 316**



Supporto a forcella inclinata

Inclined fork support

Articolo-Item	€/pc.
O 24 32 702	

 **AISI 316** **NEW**



Supporto a forcella Fork support

Articolo-Item	€/pc.	L mm.	Per tubo For pipe Ø mm.	kg.
O 24 22 101		70	22-25-30	0,170

 **AISI 316**



Supporto a forcella Fork support

Articolo-Item	€/pc.	mm.	Per tubo For pipe Ø mm.	kg.
O 24 22 102		90x40	22-25-30	

 **AISI 316**



Accoppiamento tra base e portatubo tramite sfera

Sede di rotazione in nylon. Le due parti si separano velocemente sfilando l'apposita spina di sicurezza. Costruzione in acciaio inox AISI 316 lucidato a specchio.

Articolo-Item	€/pc.	Descrizione-Description	Per tubo-For pipe Ø mm.
O 24 22 886		Base piana 93x40 mm.	-
O 24 22 884		Base apribile, per montaggio su tubo	25
O 24 22 882		Cappuccio a 90°	25
O 24 22 880		Cappuccio dritto	25

 **AISI 316** **NEW**

Coupling between base and hose holder by means of a ball

Nylon rotation seat. The two parts can be quickly separated by removing the safety pin. Mirror polished AISI 316 stainless steel construction.

