

LED courtesy light, recessless version - frontal orientation**IP65****FLUSH MOUNT**


In white plastic. Mounting via screws.

Code	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	lmm
13.178.31	12	0.5	38	2900-3200	120°	5	white	70x38x10 overhang
13.178.32	12	0.5	11.4	-	120°	5	blue	70x38x10 overhang

**Metal walkway and courtesy lights****Apus-r LED courtesy light for recess mounting - frontal orientation****IP65**


Chromed brass with clear polycarbonate diffuser. Pressure installation.

Code	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	lmm		
								Ø Recess	Ø external	Overhang
13.477.20	12/24	0.24	6	6000	80°	1	white	11	20	2
13.477.21	12/24	0.24	3	-	70°	1	blue	11	20	2
13.477.22	12/24	0.24	4	-	80°	1	red	11	20	2

**LED courtesy light for recess mounting - frontal orientation****IP65****AISI 316**


In mirror-polished micro-cast stainless steel. Polycarbonate lens. Pressure mounting.

Code	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	lmm		
								Ø Recess	Ø external	Overhang
13.429.04	12/24	0.3	6	6000	25°	1	white	25	40	3
13.429.05	12/24	0.3	3	-	25°	1	blue	25	40	3

**Alcor LED courtesy light for recess mounting - downward orientation****IP67****AISI 316**

Machined stainless steel body. Snap mounting.

Code	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	lmm		
								Ø Recess	Ø external	Overhang
13.425.90	12/24	0.1	20	3000	100°	1	white	25.4	38	12
13.425.91	12/24	0.2	10	-	100°	1	blue	25.4	38	12
13.425.92	12/24	0.2	10	-	100°	1	red	25.4	38	12

**Tilly LED courtesy light for recess mounting - frontal or downward orientation****IP67**

White plastic body, mirror-polished stainless steel front panel. Snap mounting.

Code	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	lmm		
								Ø Recess	Ø external	Overhang
13.426.01	12/24	0.5	25	3000	360°	6	white	25.4	38	7
13.426.02	12/24	0.5	10	-	360°	6	blue	25.4	38	7
13.426.10	12/24	0.5	25	3000	180°	6	white	25.4	38	7
13.426.11	12/24	0.5	10	-	180°	6	blue	25.4	38	7



13.426.11

13.426.01