

HTX Track End



PART NO	SIZE	LENGTH		WIDTH		WEIGHT	
		mm	in	mm	in	g	oz
291219907	1	40	1 5/8	57.5	2 1/4	20	0.7
291229907	2	45	1 3/4	65	2 1/2	40	1.4

Sz 1 & 2 HTX Spares and Accessories

Cleat Assembly for End stop (Pair)



PART NO	SIZE	WORKING LOAD LIMIT	
		kg	lb
291219905	1	200	440
291229905	2	300	660

Spare Slide Rods Kit



PART NO	SIZE
291219910	1
291229910	2

Spare Rubber Buffer Kit



PART NO	SIZE
291219911	1
291229911	2


HTX Upstand Kit



PART NO	SIZE
291219901	1
291229901	2


HTX Size 1 & 2 Tracks

Drilled Plunger Track



Commonly used and particularly useful where through deck fixing is not possible, such as in double skinned boats, where fixing bolts are trapped into a plate in the deck.

Beam Track



Beam track is used when spanning cockpits and across companion way hatches. Three fixing bolts should always be used either side of the span and washers fitted under the head of the bolt and between track and deck. Some beam track can only use metric fasteners

■ Made of Aluminium 6082T6 extrusion

HTX Track Specifications and Fixing Details

PART NO	DESCRIPTION	TRACK SIZE	ACTUAL LENGTH		H		W		WIDTH (overall)		WEIGHT (per metre)		MAX SPAN BETWEEN FIXINGS / CENTRE HOLE DISTANCE		FIXINGS	
			m	ft	mm	in	mm	in			g	oz	mm	in	Metric	Imperial
29181415	Drilled Plunger Track	1	1.526	5'	20	0.78	22.0	0.86	25	0.98	658	23.21	100	3 15/16	M6	1/4"
29181420			2.026	6'8"												
29181430			3.026	9'11"												
29182415	Drilled Plunger Track	2	1.532	5'	24	0.94	26.4	1.04	31	1.22	933	32.91	100	3 15/16	M8	5/16"
29182420			2.032	6'3"												
29182430			3.032	10'												
29181315	Beam Track	1	1.5	4'11"	31	1.22	27.8	1.09			1092	38.52	700	27 9/16	M8	5/16"
29181320			2.0	6'7"												
29182315	Beam Track	2	1.5	4'11"	40	1.57	35.1	1.38			1697	59.86	800	31 1/2	M10	3/8"
29182320			2.0	6'7"												