

OSCULATI



Classic 360° pull-out pole

For vessels < 20 m. Equipped with a special base in **stainless steel AISI 316** with snap contacts. Inserting the pole into the base automatically activates the contact.

Version		Length cm	Light colour	Base mm	Halogen bulb included
Standard	with 30° light in axis				
11.160.00	11.160.20	60	Black Plastic	85x50	14.200.02 (12 V - 10 W)
11.160.01	-	60	SS	85x50	14.200.02 (12 V - 10 W)
11.160.02	11.160.22	60	White plastic	85x50	14.200.02 (12 V - 10 W)



OSCULATI



Classic 360° pull-out pole with Advance base

AISI 316

For boats < 20 m. In **polished stainless steel AISI 316**, with a base of **stainless steel 316 + rubber nylon**. Inserting the rod activates the contact.

Rod with base		Length cm	Light colour	Halogen bulb included
Standard	Flush			
11.163.00	11.163.06	100	Black Plastic	14.200.02 (12 V - 10 W)
11.163.01	11.163.07	100	SS	14.200.02 (12 V - 10 W)
11.163.02	11.163.08	100	White plastic	14.200.02 (12 V - 10 W)
11.164.00	11.164.06	60	Black Plastic	14.200.02 (12 V - 10 W)
11.164.01	11.164.07	60	SS	14.200.02 (12 V - 10 W)
11.164.02	11.164.08	60	White plastic	14.200.02 (12 V - 10 W)



OSCULATI



Utility 360° mooring light

Made of polycarbonate, for vessels < 20 m.

Code	Base Ø mm	Light colour	Light colour	Height mm	Halogen bulb included
11.134.00	60	white	Black	90	14.220.02 (12 V - 10 W)
11.134.02	60	white	white	90	14.220.02 (12 V - 10 W)
11.134.01	60	red*	Black	90	14.220.04 (12 V - 15 W)

* Light of Non-Government.

Classic 360° LED mooring light

OSCULATI

LED

Polycarbonate and AISI316 stainless steel light. For vessels < 20-m long.

Code	Light colour	Shank for pipe fitting	Ø mm	Height mm	LED bulb included
11.133.10	Black polycarbonate	-	60	74	14.223.00 (12/24 V - 1.7 W)
11.133.11	White polycarbonate	-	60	74	14.223.00 (12/24 V - 1.7 W)
11.133.13	Black polycarbonate	INCLUDED (for pipe Ø 20 mm)	60	74	14.223.00 (12/24 V - 1.7 W)
11.133.14	White polycarbonate	INCLUDED (for pipe Ø 20 mm)	60	74	14.223.00 (12/24 V - 1.7 W)
11.132.10	SS	-	64	74	14.223.00 (12/24 V - 1.7 W)
11.132.11	SS	INCLUDED (for pipe Ø 20 mm)	64	74	14.223.00 (12/24 V - 1.7 W)

